

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8892)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 14}{S\ 23}$
1917

from which

- A fir, 18" dia., bears N.16°E., 34 lks., mkd: 1/4 S14 BT.
- A fir, 30" dia., bears S.6°30'E., 50 lks., mkd: 1/4 S23 BT.

BLM remonumentation by Hans W. Thielsen, Cadastral Surveyor under Group No. 350, surveyed April 11, 1957 - (DCSO records Vol. 33 Page 13873)

The remonumentation. of the 1/4 sec. cor, of secs 14 & 23, T32S R9W as requested the District Forester of the Medford. Forest District, BLM. The Kelsey-Mule Ck Rd is to be constructed through the corner position, and it was necessary to establish reference monuments in order to perpetuate the corner position

Point for the 1/4 cor, of secs 14 and 23, determined at record distances from the remains of the original BTs as follows:

- A sawed fir stump, 20" dia., bears S.32°E., 32 lks. marked with an open blaze. (Record bearing N.16°E.)
- A sawed fir stump, 32" dia., bears S.6 1/2°E., 50 lks., marked 23 in open blaze.

No monument established at the true corner point from the corner point

An iron post, 28" long, 2 1/2" dia set 22" in the ground for a reference monument bears N.16°W., 200 lks with brass cap marked 1/4 S14 T32S R9W RM 1957 and an arrow pointing to the true corner,

from which

- A fir, 32" dia., bears S.24°W., 34 lks. marked RM 1/4 S14 BT
- A fir 31" dia., bears N.74 1/2°E., 85 lks., mkd RM 1/4 S14 BT

from the corner point

- An iron. post, 48" long, 2 1/2" dia. set 22" in the ground for a reference monument bears S.16°E., 200 lks. with brass cap marked 1/4 S23 T32S R9W RM 1957 and an arrow pointing to the true corner,

from which

- A fir 27" dia bears S.71°W., 34 lks., mkd RM 1/4 S23 BT.
- A fir 33" dia., bears S.21°E., 81 lks. mkd RM 1/4 S23 BT.

continued next page

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 5/19/2025 - C.S. File 67/60-34

Found - None

BLM brass cap RM N.16°W. 132.00 ft. (Rec 200 lks)
marked ¼ S14 T32S R9W RM 1957 and arrow pointing
to corner.

From which;

41" Hemlock S.74°W. (Rec S.24°W.) 22.4 ft (Rec 34 lks)

47" Fir N.74½°E. 56.1 ft. (Rec 85 lks)

BLM brass cap RM S.16°E. 132.00 ft (Rec 200 lks)
marked ¼ S23 T32S R9W RM 1957 with arrow pointing
to corner from which;

27" Fir stump S.71°W. 22.4 ft (Rec 34 lks)

33" Fir stump S.21°E. 53.5 ft (Rec 81 lks)

Compass decl. 14½°E.

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

N. -18111.721 E. 58528.946