

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8875-6)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 35|S 36  
1917

from which

A fir, 24" dia., bears S.33°E., 16 lks., mkd: 1/4 S36 BT.

A sugar pine, 50" dia. bears N.21°W. 48 lks. mkd: 1/4 S35 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - June 1967 - C.S. File 54/44-34

-----  
Found - 24 D.Fir, now 27", S.33°E., 10.6 ft., shows good scar.

50" S.Pine, now 54", N.21°W., 31.7 ft., scribe visible "B" Tree leaning badly, broken top.

GLO Brass Cap for 1/4 corner, properly mkd in 1917.

New BT - 18" D.Fir N.58°E. 31.0 ft. mkd. 1/4 S35 CS BT.

Note - This corner lies 130.0 ft south of ravine, running NW

Daren Cone - For: Oregon Department of Forestry - 10/2015 - M170-22

-----  
Found - 1" OD GIP with 2 1/2" BC per 1917 GLO survey. Pipe has rusted off at ground level.

Fd BC with 14" of pipe attached laying on ground next to remaining GIP.

BTs per GLO 1917 SURVEY:

24" dia. fir bears S.33°E., 10.6', now 28" DBH snag, scribe healed over, existing YMLP

50" diameter sugar pine bears N.21°W., 31.7', now 55" dia. x 2' tall stump, with no discernable scribing. Existing YMLP

BT established by DCSO 1967 RESTORATION:

18" dia. D.Fir bears N.58°E., 31.0', now missing (in old cat fire line)

Set - A 2" OD x 36" long aluminum pipe over the remaining GIP, firmly set with 10" above ground, with 4" aluminum cap marked:

STATE OF OREGON DEPARTMENT OF FORESTRY

1/4 S35|S36

10/23/15

PLS43362

continued next page

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New - 6.7" DBH D.Fir bears N.8½°E., 10.6', scribed "S36 ¼ BT", new YMLP

10.8" DBH D.Fir bears N.57½°W., 50.1' scribed "S35 ¼ BT", new YMLP.

1/2" dia. x 5' white fiber glass rod bears 1' north placed 1917 GLO BC & GIP alongside new monument.

Note -Set 5' metal "T" fence post set on line 19.2 ft north of ridge top road centerline, course N.70°E., and 571.5' South of ¼ corner scribed "PLS 43362" in flange.