

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8876)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 25, 26, 35, & 36, with brass cap mkd

T32S R9W
S 26|S 25
S 35|S 36
1917

from which

- A fir, 20" dia. bears N.58°E. 28 lks. mkd: T32S R9W S25 BT
- A fir, 40" dia bears S.40°E. 46 lks. mkd: T32S R9W S36 BT
- A fir, 36" dia. bears S.27°W. 73 lks. mkd: T32S R9W S35 BT
- A fir, 30" dia. bears N.74°W. 18 lks. mkd: T32S R9W S26 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - June 1967 - C.S. File 54/44-35

Found - GLO Brass Cap at Sec. Cor., properly marked in 1917.
20" D.Fir, now 22, N.58°E. 18.5 ft. shows good scar.
40" D.Fir, now 41" S.40°E., 30.4 ft. shows good scar
36" D.Fir, now down, S.27°W. 48.2 ft.
30" D.Fir, now down N.74°W. 11.9 ft. shows good scar
New BTs- 36" D.Fir N.55°W. 57.5 ft. mkd. T32S R9W S26 CS BT.
28" D.Fir S.68°W., 65.5 ft. mid. T32S R9W S35 CS BT.