

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8878)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 26 | S 25
1917

from which

- A laurel, 6" dia., bears S.62°E., 16 lks., mkd: 1/4 S25 BT.
- A fir, 60" dia., bears N.42°W., 14 lks., mkd: 1/4 S26 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - June 1967 - C.S. File 54/44-36

Found - 6" Laurel, now 9 stob, S.62°E. 10.6 ft. mkd. scribe visible.

60" D.Fir, now 60", N.42°W. 9.2 ft., shows good scar
GLO Brass Cap at 1/4 Cor. mkd. properly in 1917

New BT - 6" Laurel S.33°E. 7.0 ft. mkd. 1/4 S25 CS BT.