

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8878)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd

T32S R9W  
S 23 | S 24  
S 26 | S 25  
1917

from which

- A fir, 36" dia. bears N.32°E. 60 lks. mkd: T32S R9W S24 BT
- A fir, 30" dia. bears S.25°E. 90 lks. mkd: T32S R9W S25 BT
- A fir, 40" dia. bears S.52°W. 42 lks. mkd: T32S R9W S26 BT
- A sugar pine, 36" dia., bears N.5°W., 45 lks., mkd: T32S R9W S23 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - 6/1/1967 - C.S. File 54/44-16

- 
- Found - GLO Brass Cap, 1917, properly marked at Corner.  
36" Pine, now Snag, N.5°W., 29.7 ft., scribe visible T32S R9W S23 BT.  
40" D.Fir, now Snag, S.52°W., 27.7 ft., scribe visible "S26".  
36" D.Fir, now down, N.32°E., 39.6 ft., shows scar.  
30" D.Fir, now 37", S.25°E., 59.4 ft., shows good scar.

- New BTs- 36" D.Fir N.6°E., 32.8 ft. mkd. T32S R9W S24 CS BT.  
41" D.Fir S.57°W., 34.8 ft. mid. T32S R9W S26 CS BT.  
6" Chinquapin N.24°W. 22.5 ft. mkd T32S R9W S23 CSBT

Note - Corner lies 330.0 E of ridge top & 600.0 ft. south of ridge top.