

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8880)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 23 | S 24
1917

from which

- A fir, 48" dia., bears S.67°E., 50 lks., mkd: 1/4 S24 BT.
- A fir, 48" dia., bears N.57°W., 128 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - 6/1967 - C.S. File 54/44-37

Found - GLO Brass Cap for 4 corner, properly marked in 1917. 48" now 50" D.Fir, S.67°E., 33.0 ft., scribe visible "2".

48" D.Fir, now Stump, N.57°W., 84.5 ft., scribe visible "1/4 23 BT".

New BT - 10" Pine S.62°W., 12.8 ft. mkd. 1/4 S23 CS BT.

Note - This corner lies on top of large ridge, running E & W.