

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8880)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T32S R9W
S 14 | S 13
S 23 | S 24
1917

from which

- A fir, 36" dia., bears N.8°E., 127 lks., mkd: T32S R9W S13 BT.
- A fir, 36" dia., bears S.78°E., 127 lks., mkd: T32S R9W S24 BT.
- A fir, 48" dia., bears S.44°30'W., 239 lks., mkd: T32S R9W S23 BT.
- A fir, 30" dia., bears N.51°W., 122 lks., mkd: T32S R9W S14 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-15

-
- Found - GLO Brass Cap, 1917, properly marked at corner.
- 36" D.Fir, now stump, N.8°E. 83.8 ft., no scar visible.
 - 36" D.Fir, now stump, S.78°E. 83.3 ft., scribe visible "9W"
 - 48" D.Fir, now stump, S.44½°W., 157.4 ft., shows good scar.
 - 30", now 37" D.Fir, N.51°W. 80.5 ft., shows good scar.

- New BTs-
- 12" D.Fir N.19°W. 15.0 ft. mkd. T32S R9W S14 CS BT.
 - 6" D.Fir N.72°E., 8.0 ft. mkd. T32S R9W S13 CS BT.
 - 8" D.Fir S.11°E., 24.7 ft. mkd. T32S R9W S24 CS BT.
 - 9" D.Fir S.28°W., 25.5 ft. mkd. T32S R9W S23 CS BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and Jeff Lorsung - 6/19/2025 - C.S. File 67/60-50

-
- Found - GLO 2½" Brass cap proj 16". Add rough mound of stone around base.
- 30"x2 ft rotted, broken fir stump N.8°E. 83.8 ft blaze gone
 - 34"x8 ft rotted sawn fir stump S.78°E. 83.3 ft
 - 45"x3½ ft rotted sawn fir stump S.44½°W. Dist not checked, trees on line.

continued next page

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40" D.Fir N.51°W. 82.5 ft (Rec 80.5 ft) Dist to 3½" mag nail set left side center
22" D.Fir N.19°W. 15.0 ft fully healed double blaze.
Add 3½" mag nail right side center.
11" D.Fir N.72°E. 8.0 ft fully healed double blaze.
Add 3½" mag nail right side center.
17" D.Fir S.11°E. 24.7 ft fully healed double blaze.
Add 3½" mag nail right side center.
19" D.Fir S.28°W. 25.5 ft fully healed double blaze.
Add 3½" mag nail right side center.

Notes - Corner is approx. 150 ft east of dirt spur road.
Mon. on moderate N.W. slope in old fir regrowth.

Compass decl. 14½°E.
OGRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
42°46'58.75785 N
123°42'59.50383 W