

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION WC Cor. Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8884)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T32S R9W
S 2 | S 1
S 11 | S 12
1917

from which

- A fir, 26" dia. bears N.86°E. 120 lks. mkd: T32S R9W S1 BT
- A fir, 7" dia., bears S.8°E., 82 lks. mkd: T32S R9W S12 BT
- A laurel, 12" dia., bears S.4°W., 148 lks., mkd: T32S R9W S11 BT.
- A laurel, 5" dia., bears N.68°W., 30 lks., mkd: T32S R9W S2 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - 6/1967 - C.S. File 54/44-45

Found - 26", now 30" D.Fir, N.86°E., 79.2 ft., shows good scar.

7", now 28" D.Fir, S.8°E., 54.1 ft. shows faint scar
12", now 19" Laurel S.4°W., 97.7 ft., opened for scribe "T3".

No trace of NW BT nor Brass Cap as this corner falls in middle of old jeep road.

Set Brass Cap for Wit. Corner Mkd: County Surveyors T32S R9W
Office WC 15' East to
1967 S 2 | S 1
S 11 | S 12

New BTs- 13" Laurel S.11½°W., 12.0 ft. mkd. WC T32S R9W S11 CS BT.

6" Laurel N.11°W. 10.0 ft. mkd. WC S 2 CS BT.

Rescribed- 28" D.Fir S.23½°E., 58.5 ft. mkd. WC T32S R9W S12 CS BT.