

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8886)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 2 | S 1
1917

from which

A sugar pine, 24" dia. bears S.18°E. 116 lks. mkd: 1/4 S1 BT
A laurel, 9" dia., bears S.10°30'W., 91 lks., mkd: 1/4 S2 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-47

Found - GLO brass cap at 1/4 corner, properly mkd. in 1917. 24" now 36" S.Pine, S.18°E., 76.6 ft., shows good scar.

No trace of SW 9" Laurel BT.

New BT - 6" Tan Oak S.49 1/2°W., 3.4 ft., scribed 1/4 S2 CS BT.