

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only, (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12187)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor.of secs. 1 and 2, with brass cap mkd:

S 2 | S 1
T32 | R9W
1917

from which

A Fir 16" dia., bears S.21°E., 12 lks. dist. mkd. T32S R9W S1 BT.

A Fir 10" dia., bears S.30°W., 8 lks. dist. mkd. T32S R9W S2 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - March/April 1967 - C.S. File 54/32-62

Found - GL0 brass cap at cor., properly mkd., in 1917.
10" now 13" D.Fir S.30°W., 5.3 ft., shows good scar
16" now 18" D.Fir S.21°E., 7.9 ft., tree opened earlier, scribe visible "T32S R9W S1", face cut.

Reblazed and rescribed:

18" D.Fir S.21°E., 7.9 ft. mkd. T31S R9W S1 CS BT
Corner lies 10.0 ft. East of very small ravine.