

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 638700

PRIMARY CORNER DESCRIPTION AP N. Bdy. Section 1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 19 Page(s) 8167) (also filed with notes in C.S. File 64/76-2)

Set a stone 14x12x5 ins., 10" in the ground for the ¼ sec. cor. from which

- A Fir 18" dia., bears N.45°E., 38 lks. dist. mkd. ¼ S BT
- A Fir 16" dia., bears S.45°E., 19 lks. dist. mkd. ¼ S BT

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12187)

Intersect the point for old ¼ sec. cor. of sec. 1, located by reference to the bearing trees as described by the surveyor general. I change this cor. to an angle point and perpetuate it as follows:

At exact cor. point

Set an Iron post 3 ft. long, 1" dia., 26" in the ground, for angle point with brass cap mkd. AP
1917

from which

- A Fir 24" dia., bears N.43°E., 38 lks. dist. mkd. A P BT.
(Old BT)
- A Fir 30" dia., bears S.41°E., 19 lks. dist. mkd. A P BT.
(Old BT)