

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8877)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 25  
S 36  
1917

from which

A chinquapin, 10" dia. bears N.9°E., 15 lks. mkd: 1/4 S25 BT  
A fir, 20" dia., bears S.12°W., 34 lks., mkd: 1/4 S36 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - June 1967 - C.S. File 54/44-31

-----  
Found - GLO brass cap at 1/4 corner, properly marked in 1917. 10" Chinquapin, now 14" N.9°E., 9.9 ft., scribe visible, "1/4 S24 B" face rotten. 20" D.Fir, now 28" stump, S.12°W., 35.4 ft., opened for scribe, S25 BT.

New BTs- 10" D.Fir S.67 1/2°W., 23.3 ft., mkd: 1/4 S36 CS BT.  
16" D.Fir, N.43°E., 25.0 ft., mkd: 1/4 S25 CS BT.

Note - By ring count, places trees at proper time. Also calls are good.