

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8881)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 13}{S\ 24}$
1917

from which

- A fir, 16" dia., bears S.85°E., 69 lks., mkd: 1/4 S24 BT.
- A fir, 36" dia., bears N.48°30'W., 62 lks., mkd: 1/4 S13 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-17

Found - GLO brass cap, 1917, properly marked at 1/4 Corner. 16" now 24" D.Fir, S.85°E., 45.5 ft., shows good face.

36" now 38" D.Fir stump, N.48½°W., 40.9 ft., shows scribing "1/4 S13 CS BT"

New BT - 12" D.Fir N.29°W., 15.6 ft., mkd: 1/4 S13 CS BT.

Note - 1/4 corner lies 90 ft. East of road.