

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8883)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 S 12
S 13
1917

from which

A fir, 18" dia., bears S.84°W., 106 lks., mkd: 1/4 S13 BT.
A fir, 10" dia., bears N.9°W., 40 lks., mkd: 1/4 S12 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - 6/1967 - C.S. File 54/44-54

Found - GLO Brass Cap at 1/4 corner, properly marked in 1917. 10", now 22" D.Fir, N.14°W. (Record N.9°W.) 26.4 ft., shows good scar
18", now 28" D.Fir, S.84°W. 70.0 ft., shows good scar.

Reset Brass Cap, cap was badly bent, we straighten & reset. New BTs- 14" D.Fir S.71°E., 6.8 ft. mkd. 1/4 S13 CS BT.

Rescribed: 22" D.Fir N.14°W., 26.1. ft. Mkd. 1/4 S12 CS BT.

Note - This corner lies approx. 50.0 ft. south of ridge top-running E - W.