

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8885)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S}{S} \frac{1}{12}$
1917

from which

A laurel, 5" dia., bears N.69°E., 13 lks., mkd: 1/4 S1 BT.
A laurel, 5" dia., bears S.22°W., 57 lks., mkd: 1/4 S12 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - 7/1967 - C.S. File 54/44-56

Found - 5" Laurel, now down & rotten, N.48°E., 8.6 ft. (Record N.69°E.) found definite scribe marks but not legible.

5" now 8" Laurel, S.12°W. (Record S.22°W.) 37.6 ft., face rotted out, high blaze on tree which is typical work.

GLO Brass Cap at 1/4 corner properly marked in 1917.

New BTs- 7" Tan Oak N.15°W., 6.2 ft. mkd. 1/4 S1 CS BT.

6" D.Fir East 28.8 ft. mkd. 1/4 S12 CS BT.

Note - This corner lies west of high ridge 103.0 ft.