

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 641100

PRIMARY CORNER DESCRIPTION A P on So. Bdy. Sec. 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12197)

Intersect the old standard $\frac{1}{4}$ sec. cor., which is a basalt stone, firmly set, mkd. and witnessed as described by the surveyor general. I change this cor. to an angle point and perpetuate it as follows: alongside the old cor.

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for angle point, with brass cap A P
1917

from which

A Laurel 20" dia., bears N.7°E., 48 lks. dist. mkd. AP BT
(Old BT)

A Fir 20" dia., bears N.35°W., 42 lks. dist. mkd. AP BT.
(Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-50

(This corner lies 62.0 ft. East of $\frac{1}{4}$ corner sec. 36 only)
Corner in good condition. All trees tagged. Also, 140.0 ft. W. of creek 2 lks.

Found - Orig. 20" now 26" D.Fir N.35°W., 27.7 ft. shows good scar.

Orig. 20" now 22" Laurel N.7°E., 31.7 ft., open fce and rotted part of "B" legible.

1917 GLO brass cap at A.P., properly marked.

Rescribed, 22" Laurel N.7°E., 31.7 ft. mkd. A.P. CS BT.