

PRIMARY CORNER DESCRIPTION SE. Cor. for Sec. 36, T31-9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

David Edwards - For Plum Creek Timberlands - 5/2009 - M159-23

Found - 1918 GLO brass cap.
8" dia., Madrone bears S.42°E., 21.2'
5" dia., dead madrone bears N.13°W., 26.0'
New BT - 7" dia., fir bears N.32°W., 31.4 ft.
Set 6 ft. steel post 2' north

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2797, surveyed July/Aug 2015 - (DCSO records Vol. 58 Page(s) 23431-2)

The cor. of T. 31 S., Rs. 8 and 9 W., perpetuated by the Douglas County Surveyor's Office in 1967, as shown on the Douglas County Surveyor's Office corner renewal record in T. 31 S., R. 8 W., point identifier No. 100100, and further perpetuated by Edwards, in 2009; monumented with an iron post, 3" dia., firmly set, projecting 16" above the ground, in a collar of stone, with brass cap (properly) mkd. from which the remains of an original bearing tree
A sawed and rotted fir stump, 33" dia., bears N.26°W., 34.3 ft., with a healed blaze.
and BTs mkd. by the Douglas County Surveyor's Office
A madrone, 9" dia., bears S.43¼°E., 21.4 ft. with no marks visible on rotted, partially healed double blazes.
A madrone snag, 6" dia bears N.13½°W. 25.2 ft with no marks visible on rotted, partially healed double blazes.
and a bearing tree mkd. by Edwards
A fir, 9" dia., bears N.32½°W., 31.4 ft., with a healed blaze.
and a new bearing tree
A fir, 5" dia., bears N.20¼°E., 20.9 ft., mkd. X at breast height and BT at the base.
A steel post set by Edwards, projecting 4.5 ft. above the ground, is North, 2 ft., of the cor.
Each new bearing tree has a 2½" x ¼" magnetic nail (Mag Nail) driven at the base on right side center.