

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 662100

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1, T33-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12197)

Intersect the closing cor. of Tps. 33 S., Rs. 8 and 9 W., which is a sandstone, 5x8x8 ins. above ground, firmly set, marked and witnessed as described by the survey, (vis.: 6 notches on E., W., and S. edges), from which
A Fir 10" dia., bears S.78°E., 46 lks. dist. mkd. T33S R8W S6 BT.
A Pine 30" dia., bears S.30°W., 29 lks. dist. mkd. T33S R9W S1 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-52

Found - Original 5x8x8 Corner stone with 4 notches on W. side.
10" now 11" D.Fir S.78°E., 30.4 ft., opened and found scribe.
30" now 36" Pine, S.30°W., 19.1 ft., shows good face.

Set Brass cap at cor. mkd: County Surveyors Office
R Doug. Co. R
9 T 32 8
W S 1 | S 6 W
Jos. Co.
1967

Rescribe - 11" D.Fir S.78°E., 30.4 ft. mkd. T33S R8W S6 CS BT.