

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8775)

Set a stone 14x12x7 ins., 10" in the ground, for the 1/4 sec. cor. mkd. 1/4 on W. side, from which
A Fir 8" dia., bears N.69°E., 59 lks. dist. mkd. 1/4 S BT
A Fir 20" dia., bears S.84°W., 57 lks. dist. mkd. 1/4 S BT

GL0 Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8837-38)

Intersect at the old 1/4 sec. cor., which is a basalt stone, 5x12x7 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general, except for some discrepancies in the position of the bearing trees. I change this cor. to refer to sec. 31 only and perpetuate it as follows: alongside the old cor.
Set an Iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 cor. of sec. 31, T32S R8W only, with brass cap marked:

1/4
|
S 31
1917

from which
A Fir 18" dia., bears N.72°E., 58 lks. dist. mkd. 1/4 S31 BT (Old BT)
A Fir 12" dia., bears S.86°E., 74 lks. dist. mkd. 1/4 S31 BT (New BT)

Survey by Robert Thompson - Wit: R. Gledhill - Feb. 28, 1961 - C.S. File 51/181-2

I find 1" I.P. with brass cap, from which a
18" D.Fir now 20", bears N.72°E., 58 lks. (OBT)
12" D.Fir S.86°E., 74 lks., now 16", cut stump.
To renew, I scribe a:
9" D.Fir N.35°E., 18.5 ft. "1/4 S31 BT".

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-33

Found - GL0 brass cap, 1917, properly marked.
Orig. 18" D.Fir, now snag, N.72°E., 38.3 ft., shows scar.
12" D.Fir, now stump, S.86°E., 48.8 ft.
9" D.Fir now dead, N.35°E., 18.5 ft., scribe visible
(Cont. Next Page)

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700139

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only, T32-8

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New BT - 6" D.Fir N.51°E., 52.6 ft. mkd. ¼ S31 CS BT.
Corner lies in clear cut area, approx. 30 ft. N. of ravine on
W. edge of skid road. (Lies S. of E. 1/4 Cor. for Sec. 36)