

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8840)

Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 cor. of sec. 25 only, with brass cap mkd.

1/4
S25
1917

from which

A Fir 36" dia., bears S.32°W., 102 lks. dist mkd. 1/4 S25 BT
A Chinquapin 8" dia., bears N.18°W., 56 lks. dist. mkd. 1/4 S25 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-28

Found - 36" now 39" D.Fir S.32°W., 67.3 ft., shows good scar
8" Chinquapin, now down, N.18°W., 37.0 ft., rotten face, shows scribing.

1917 GLO brass cap, properly mkd.

New BT - 8" Chinquapin N.89°W., 20.0 ft. mkd. 1/4 S25 CS BT.