

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8841)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 24 and 25, with brass cap marked

T32S
S24
S25
R9W
1917

from which

A Laurel 6" dia., bears S.82°W., 46 lks. dist. mkd. T32S R9W S25 BT.

A Fir 24" dia., bears N.71°W., 70 lks. dist. mkd. T32S R9W S24 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-38

Found - 1917 GLO brass cap, properly marked.
6" Laurel, now dead, S.82°W., 30.4 ft., scribe visible "9W 25 BT"
24" now 28" D.Fir N.71°W., 46.2 ft., shows good scar
New BT - 5" D.Fir S.14°W., 5.7 ft. mkd. S25 CS BT.
Corner lies on top of spur running E. & W.