

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700334

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 19 only, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8777)

Set a stone 14x12x8 ins., 10" in the ground for the ¼ sec. cor. mkd. ¼ on W. side, from which
A Yew 5" dia., bears N.45°E., 14 lks. dist. mkd. ¼ S BT.
A Fir 30" dia., bears S.76°W., 21 lks. dist. mkd. ¼ S BT

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8842)

Intersect the old ¼ sec. cor., which is a basalt stone, 5x12x8 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general, except that the bearing trees are now dead. I change this cor. to refer to sec. 19 only and perpetuate it as follows: alongside the old cor. Set an iron post 3 ft. long, 1" dia., 26" in the ground, for ¼ cor. of sec.19, T32S R8W only with brass cap mkd.

¼
S19
1917

from which

A Laurel 10" dia., bears N.59°E., 46 lks. dist. mkd. ¼ S19 BT (New BT)
A Fir 8" dia., bears S.89°E., 35 lks. dist. mkd. ¼ S19 BT (New BT)