

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8842)

-----  
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 24 only, with brass cap mkd.

1/4  
S24  
1917

from which

A Fir 6" dia., bears S.60°W., 42 lks. dist. mkd. 1/4 S24 BT

A Fir 24" dia., bears N.29°W., 21 lks. dist. mkd. 1/4 S24 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1967 - C.S. File 54/44-62

-----  
Found - 1917 GLO brass cap, properly marked.  
24" now 30" D.Fir N.29°W., 13.9 ft., shows good scar.

6" D.Fir, now out of place due to small slide, S.60°W., 27.2 ft., almost dead, shows scar.

New BT - 8" Yew S.15°W., 10.2 ft., mkd. 1/4 S24 CS BT.