

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700429

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8778)

-----  
Set a Fir post 3 ft. long, 3" sq., 20" in the ground for the 1/4 sec. cor. mkd. 1/4 on W. side, and from which  
A Fir 48" dia., bears N.71°E., 65 lks. dist. mkd. 1/4 S BT.  
A Sugar Pine 36" dia., bears N.36°W., 42 lks. dist. mkd. 1/4 S BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8844)

-----  
Intersect at the old 1/4 sec. cor, which is a decayed and partly burned post, witnessed as described by the surveyor general. I change this cor. to refer to sec. 18 only and perpetuate it as follows: alongside the old cor.  
Set an iron post 3 ft. long, 1" dia., 26" in the ground for 1/4 cor., with brass cap mkd.  $\frac{1}{4}$   
S18  
1917  
from which  
A Fir 48" dia., bears N.71°E., 65 lks. dist. mkd. 1/4 S18 BT (Old BT)  
A Sugar Pine 16" dia., bears S.69°E., 97 lks. dist. mkd. 1/4 S18 BT (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1967 - C.S. File 54/44-57

-----  
Found - 1917 GLO brass cap, properly marked.  
48" D.Fir, now 52" stump, N.71°E., 42.9 ft., opened and shows good scribe "1/4".  
16" Sugar Pine now 17" stump, S.69°E., 64.0 ft., shows good scar.  
New BTs- 5" Tan Oak S34°W., 9.6 ft. mkd. S18 CS BT.  
48" Sugar Pine N.30°W., 30.4 ft. mkd. 1/4 S24 CS BT.  
There are no other trees in range 8 to scribe.  
Corner lies on the W. of a cutting line.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 6/4/2025 - C.S. File 67/60-45

-----  
Found - 2 1/2" GLO brass cap proj 7" (property mkd)  
Sawn partly rotted 52"x3ft D.Fir stump N.71°E.  
42.9 ft open face scribe 1/4 visible.  
Continued next page

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700429

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Sawn 16"x3½ ft sugar pine stump. S.69°E. 64.0 ft.  
Bark gone, shows good scar.  
9" Chinquapin (Rec tan oak) S.34°W. 9.6 ft fully  
healed double blaze.  
44"x12 ft broken snag sugar pine. N.30°W. 30.4 ft.  
Portion of tree broken off. Fallen on face.  
Notes - Mon is approx 12 ft east of sharp curve in main  
dirt road.  
Corner in older fir, chinquapin, and tan oak.  
Regrowth on steep N.N.E. slope.  
Compass decl. 14½°E.  
OGRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
42°47'18.19607 N.  
123°41'50.03590 W.