

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8845-46)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 12 and 13, with brass cap mkd. T32S

S12
S13
R9W
1917

from which

A Fir 5" dia., bears S.20°W., 45 lks. dist. mkd. T32S R9W S13 BT.

A Fir 12" dia., bears N.3°30'W., 192 lks. dist. mkd. T32S R9W S12 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-41

Found - 12" now 19" D.Fir N.3½°W., 126.7 ft., shows good scar.

No trace of SW. BT.

1917 GLO brass cap, properly marked.

New BT - 9" D.Fir S.62°W., 15.0 ft. mkd. T32S R9W S13 CSBT

No other good trees closer. (NW quad)

Corner lies on top of ridge, approx. 260 ft. N. of Jeep road.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 6/18/2025 - C.S. File 67/60-44

Found - 2½" GLO brass cap proj 15" set solid.

28" D.Fir N.3¾°W. 126.7 ft (Dist. not checked. Trees on line.) Shows good scar.

29" D.Fir S.62°W. 15.0 ft fully healed double blaze.

Add 3½" mag nail right side center.

New - 5" D.Fir S.6½°W. 5.7 ft scribed "X" BT on double blaze.

10" Chinquapin N.73°W. 24.0 ft scribed T32S R9W S12 BT on double blaze.

Both trees have 3½" mag nail right side center.

Notes - Corner is on top of ridge approx 175 ft north of gravel road.

Mon on mild S.E. slope in old fir, chinquapin regrowth.

Compass decl. 14½°E.

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

42°47'51.23824" N. 123°41'50.45021" W.