

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700526

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 7 only, T32-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8779)

-----  
Set a stone 14x10x7 ins., 10" in the ground for the ¼ sec. cor., marked ¼ on W. side, and from which  
A Laurel 5" dia., bears S.86°E., 43 lks. dist. mkd. ¼ S BT  
A Fir 6" dia., bears S.16°W., 13 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8846-47)

-----  
Intersect the point for old ¼ sec. cor., located by reference to the SW. bearing tree; all other traces of the cor. have disappeared. I change this cor. to refer to sec. 7 only and perpetuate it as follows: at the exact cor. point  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ cor. of sec. 7, with brass cap mkd. ¼  
S 7  
1917

from which  
A Sugar Pine 30" dia., bears N.23°E., 76 lks. dist., mkd. ¼ S7 BT (New BT)  
A Fir 5" dia., bears S.26°E., 8 lks. dist. mkd. ¼ S7 BT (New BT)