

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8847)

Set an iron post 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 12 only, with brass cap mkd.

1/4 |
S12 |
1917

from which

A Fir 36" dia., bears S.77°30'W., 125 lks. dist. mkd. 1/4 S12 BT.

A Laurel 6" dia., bears N.37°W., 80 lks. dist. mkd. 1/4 S12 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1967 - C.S. File 54/44-64

Found - 1917 GLO brass cap, properly mkd.
36" now 42" D.Fir S.27°W. (Rec. S.77½°W.) 82.5 ft., shows good scar.

6" now 10" Laurel N.37°W., 52.8 ft., shows good scar
New BTs- 9" Pine S.22°W., 27.1 ft. mkd. 1/4 S7 CS BT.
10" Pine N.85°W., 18.7 ft. mkd. 1/4 S7 CS BT.