

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8848)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 1 and 12, with brass cap mkd. T32S

S1
S12
R9W
1917

from which

A Fir 60" dia., bears S.50°W., 56 lks. dist. mkd. T32S R9W S12 BT.

A Sugar Pine 48" dia., bears N.87°W., 94 lks. dist. mkd. T32S R9W S1 BT.

David Edwards - Crew: Brant Miller & Eric Sprinkle - 1/4/2019
- C.S. File 65/102-10

Found - Standard 1917 GLO iron pipe with brass cap.
A 60" dia. Fir with no visible scribes or marks bears S.50°W., 37.0'

A 50" dia. Sugar Pine snag with visible partial scribe marks bears N.87°W., 62.0'

New - A 6" dia. Tan Oak scribed "T32S R9W S1 BT" bears N.17°W., 18.6'

A six foot steel post is set 2 feet North.

Note - Declination, 15° East