

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T32-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8780)

Set a stone 14x12x10 ins., 10" in the ground for the ¼ sec. cor. mkd. ¼ on W. side, and from which
A Live Oak 5" dia., bears N.28°E., 21 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears S.52°W., 11 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8848-49)

Intersect at the old ¼ sec. cor. which is a basalt stone, 14x12x10 ins. loosley let, mkd. and witnessed as described by the surveyor general, with the exception, that the NE. bearing tree is a Tan Oak instead of a Live Oak. I change this cor. to refer to sec. 6 only, and perpetuate it as follows: alongside the old cor.
Set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 6 only, with brass cap mkd. ¼
S6
1917
from which
A Tan Oak 7" dia., bears N.30°E., 23 lks. dist. mkd. ¼ S6 BT. (Old BT)
A Fir 24" dia., bears S.62°E., 62 lks. dist. mkd. ¼ S6 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1967 - C.S. File 54/44-65

Found - 24" now 30" D.Fir windfall, S.62°W., 40.9 ft. (BT was about 50 ft. down the hill). There was a good stump hole to get the brg. & dist. from, shows good scribe "¼".
Other BT gone.
1917 GLO brass cap, properly marked.
New BTs- 12" Hemlock N.25°E., 50.6 ft. mkd. ¼ S6 CS BT.
10" Hemlock N.36°E., 30.6 ft. mkd. ¼ S6 CS BT.
Corner lies 50.0 ft. East of creek.

Fd. BC & 2 1967 BTs by D.Edwards 3/2011 - M162-26