

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; & 12 & 13, T33-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by McKenzie and Eckleson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 21 Page(s) 8923)

-
- Set post for cor. to secs. 7, 12, 13 and 18, from which
- A Fir 10" dia., bears S.60°W., 34 lks. dist.
 - A Cedar 12" dia., bears N.45°W., 26 lks. dist.
 - A Cedar 18" dia., bears N.50°E., 54 lks. dist.
 - A Cedar 12" dia., bears S.45°E., 2 lks. dist.

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8926)

-
- Set a basaltic stone 24 x 16 x 14 ins., 18" in the ground, for cor. to secs. 7, 12, 13, and 18, marked with 4 notches on S. sides and 2 notches on N. side, from which
- A Fir 24" dia., bears N.56°E., 31 lks. dist., marked T33S R4W S7 BT.
 - A W.Fir 10" dia., bears S.41°E., 32 lks. dist., marked T33S R4W S18 BT.
 - A Cedar 16" dia., bears S.12°W., 30 lks. dist., marked T33S R5W S13 BT.
 - A W.Fir 18" dia., bears N.15°W., 31 lks. dist., marked T33S R5W S12 BT.

BLM Resurvey by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, under Group #'s 350 and 818, surveyed Aug. 1973/May 1974 - (DCSO records Vol. 38 Page(s) 15627-28)

-
- The Sec. cor., on the E. bdy. of the Tp., monumented with the original basalt stone, 24 x 16 x 14 ins., firmly set 18" in the ground, mkd. with 2 notches on N. and 4 notches on S. edges, from which the original bearing trees:
- A Fir 31" dia., bears N.56°E., 31 lks. dist., with healed double blaze.
 - A W.Fir 15" dia., bears S.39°E., 32 lks. dist., with healed double blaze. (Rec. S.41°E.)
 - A Cedar 21" dia., bears S.12°W., 30 lks. dist., with healed double blaze.
 - A W.Fir 20" dia., bears N.15°W., 29½ lks. dist., with healed double blaze.
- At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked
(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7 & 18; 12 & 13, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 33 S
R 5 W R 4 W
S 12 S 7
S 13 S 18
1974

from which new bearing trees
A Yew 6" dia., bears S.60°E., 21 lks. dist., mkd. T33S R4W
S18 BT.
A Cedar 11" dia., bears N.68°W., 59½ lks. dist., mkd. T33S
R5W S12 BT.
Deposit corner stone alongside iron post.