

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T33-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by McKenzie and Eckleson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 21 Page(s) 8924)

-
- Set post for cor. to secs. 1, 6, 7 and 12, from which
- A Y.Pine 24" dia., bears N.10°E., 56 lks. dist.
 - A Cedar 30" dia., bears N.15°W., 55 lks. dist.
 - A Fir 16" dia., bears S.60°W., 36 lks. dist.
 - A Laurel 12" dia., bears S.48°E., 52 lks. dist.

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8927)

-
- Set a basaltic stone 14 x 12 x 8 ins., 10" in the ground, for cor. to ses. 1, 6, 7 and 12, marked with 5 notches on S. and 1 notch on N. edges, from which
- A Fir 18" dia., bears N.59°E., 57 lks. dist., marked T33S R4W S6 BT.
 - A Y.Pine 30" dia., bears S.41°E., 67 lks. dist., marked T33S R4W S7 BT.
 - A Matherone 6" dia., bears S.42°W., 59 lks. dist., marked T33S R5W S12 BT.
 - A Matherone 5" dia., bears N.21°W., 39 lks. dist., marked T33S R5W S1 BT.

BLM Remonumentation by James E. Jelley, Cadastral Surveyor, under Group #350, surveyed April 1962 - (DCSO records Vol. 33 Page(s) 13921C)

The Sec. cor., monumented with a basalt stone 14 x 12 x 8 ins., firmly set, 10" in the ground, marked with 1 notch on N. and 5 on S. edges, from which the remaining original bearing trees:

- A Fir 22" dia., bears N.59°E., 57 lks. dist., with healed blaze.
- A Pine 36" dia., bears S.41°E., 67 lks. dist., with healed blaze.
- A Madrone 12" dia., bears N.21°W., 39 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked

T 33 S
R 5 W R 4 W
<u>S 1 S 6</u>
S 12 S 7
1962

(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12, T33-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
A Hemlock 20" dia., bears S.50°W., 68 lks. dist., mkd.
T33S R5W S12 BT.
Deposit the original corner stone alongside the iron post.

1962 Brass cap Fd. OK, BLM Resurvey by Lynn M. Roseberry,
Cadastral Surveyor - Under Group #723 Surveyed, Nov/Dec. 1970
- (DCSO records Vol. 36 Page(s) 14826-27)

Fd. Ok by Ken Hoffine, 3/2005 - M147-57 A&B