

PRIMARY CORNER DESCRIPTION C C to Sec. 6; and S. 1 of T33-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8929)

The closing cor. point to secs. 6 and 1, Set a basaltic stone, 14 x 12 x 6 ins., 10" in the ground, marked C C with 6 notches on S., E. and W. edges, from which
A Fir 8" dia., bears N.46°E., 24 lks. dist., marked C C T33S Rs 4 and 5 W BT.
A Fir 10" dia., bears S.77°E., 16 lks. dist., marked T33S R4W S6 BT.
A Fir 12" dia., bears S.39°W., 40 lks. dist., marked T33S R5W S1 BT.

(Pages 8959-60)

I return to the cor. established for the NW cor. of Tp. 33 S R4W on Tp. line between secs. 1 and 6 which is a basaltic stone 4 x 12 x 6 ins. above ground, mkd. CC with 6 notches on S. E. and W. edges. I destroy the SW and NE trees referring to the closing cor. for the NW cor. to Tp. 33 S. R 4 W and from which remains

A Fir 10" dia., bears S.77°E., 16 lks. dist., marked T33S R4W S6 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Wm. Stoffel, Mike Darby, Mike Stone, crew - June 1964 - C.S. File 53/52-65

Found - Rock as described, in mound of rocks.
Fir snag N.46°E., 15.8 ft. scribing visible "T 33 SR 4 & 5 W S1 & 6 BT".
Fir snag S.77°E., 10.6 ft. part of face exposed, but no scribing visible.
D.Fir, now 15" dia., S.39°W., 26.4 ft. Scribe visible on previously opened face. "3S R5W S1". Tree in good condition. A vertical rock cliff approx. 10 ft. high between this tree and corner.

Set a Brass cap, on top of bedrock, mkd:

County Surveyors Office

T 32 S
R S 31 R
5 S1 | S6 4
W W

T 33 S
1964

Cap not oriented correctly. Erect mound of rocks around pipe.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Sec. 6; & S. 1, T33-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BT - 9" D.Fir S.65°E., 25.0 ft. mkd. T33S R4W S6 CS BT.
Corner lies on very steep, rocky NW slope.

BLM resurvey by Gawron, Jelley and Aanrud, Cadastral Surveyors, under Group #'s 350 and 566, surveyed March 1965/Dec. 1967 (DCSO records Vol. 34 Page(s) 13977)

The cor. of Tps. 33 S., Rs. 4 and 5 W., only, on the S. bdy. of sec. 31, T32S R4W., monumented with an iron post, 1½" dia., supported in a mound of stone, 5 ft. base, 4 ft. high, with brass cap mkd. County Surveyors Office T32S S31 R5W S1 S6 R4W T33S 1964, from which the original bearing trees mkd. by Sharp:

- A D.Fir snag 8" dia., bears N.46°E., 24 lks. dist., mkd. T33S R4W & 5W BT on a weathered blaze.
- A D.Fir snag 10" dia., bears S.77°E., 16 lks. dist., mkd. T33S R4W S6 BT on a weathered blaze.
- A D.Fir 16" dia., bears S.39°W., 40 lks. dist., with healed blaze.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16540)

The cor. of Tps. 33 S., Rs. 4 and 5 W., perpetuated and recorded by Milo E. Godfrey, in 1964, monumented with an iron post, 1½" dia., firmly set, projecting 6" above a mound of stone, 5 ft. base, 2 ft. high with properly mkd. Brass cap. from which the remains of the original bearing trees:

- A Fir snag 10" dia., bears N.46°E., 25 lks. dist., with scribe marks T33S R4W visible on partially healed double blaze. (Rec. 24 lks.)
 - A Fir snag 12" dia., bears S.74 3/4°E., 17 lks. dist., with scribe marks T33S R4W visible on weathered double blaze. (Rec. S.77°E., 16 lks.)
 - A Fir 13" dia., bears S.42 3/4°W., 40 lks. dist., with healed double blaze. (Rec. S.39°W.)
- and the remains of a bearing tree mkd. by Godfrey
- A Fir snag 8" dia., bears S.66°E., 38 lks. dist., with scribe marks T33S R4W S6 CS BT visible on weathered double blaze.
- and a new bearing tree
- A Fir 25" dia., bears S.72°E., 58 lks. dist., mkd. T33S R4W S6 CC BT.

Fd. Ok by Ken Hoffine, 3/2005 - M147-57 A&B