

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8944)

Set a basaltic stone 12 x 7 x 7", 12" in the ground, for ¼ sec. cor. ¼ on N side, from which
A cedar, 20" dia., bears S.30°W., 55 lks., mkd: ¼ S BT.
A cedar, 3" dia., bears N.65°E., 11 lks., mkd: ¼ S BT.

Ken Hoffine - For: Lone Rock Timber Co. - March 2005 - M147-57 A&B

Found - 7"x7'x12" stone no marks partially set in ground in mound of stones set ½" aluminum cap marked LONE ROCK TIMBER T33S R4W 1/4 S6 S7 2004 PLS 2291 with original stone alongside in mound of stone
11" I.Cedar bears N.22°E., 8.5 ft, we scribe ¼ S6 BT & tag
10" D.Fir bears N.48¼°W., 10.7 ft, we scribe ¼ S6 BT & tag
14" D.Fir bears S.33°W., 21.4 ft, we scribe ¼ S7 BT & tag
9" D.Fir bears S.58°E., 28.68 ft, we scribe ¼ S7 BT & tag
Roothole bears N.55¼°E. 7.5 ft (rec N.65°E. 7.26 ft)
Roothole bears S31¼°E. 36.2 ft (rec S.30°W. 36.3 ft)
Corner lies in mound of stone on southwest slope.