

PRIMARY CORNER DESCRIPTION A.P. #1 on N. bdy. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by McKenzie and Eckelson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records, Vol. 20 Page 8466)

Set post for ¼ sec. corner, from which
A Fir 18" dia., bears N.30°E., 19 lks. dist.
A Fir 18" dia., bears S.27°W., 18 lks. dist.

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8946)

Intersected the standard 1/4 sec. cor. on S. bdy. of sec. 31, T32S R4W, which is a post 12" above ground 3" sq., marked S C ¼ S. on N. face, from which
A Fir 18" dia., bears N.30°E., 19 lks. dist., with well defined blazes.
A Fir 18" dia., bears S.27°W., 18 lks. dist., with well defined blazes.

Douglas Co. Surveyors Office - John M. Powell, W. Penley, J. Heritage, crew - 1970 - C.S. File 54/114-36

Found - 18" D.Fir now stob, N.30°W., 15.7 ft. (Rec. N.30°E., 12.9 ft.) scribe visible.
18" D.Fir now stob, S.27°W., 11.9 ft. scribe visible.

By facing up trees, assume S. tree correct, also hit old E-W blazed line.

Set Brass cap at cor. mkd: County Surveyors Office
T 32 S S 31
R4W T 33 S S ¼ C
1970

New BTs -6" D.Fir N.39°E., 12.5 ft. mkd. "S ¼ C S31 CS BT"
6" D.Fir N.26°W., 28.2 ft. mkd. "S ¼ C S31 CS BT"

Old mound of stones is 1.5 ft., not called for in notes, but look like they were put there.

BLM resurvey by Lynn Roseberry and Rollin Aanrud, Cadastral Surveyors, under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16537-38)

The former standard 1/4 sec. cor. of sec. 31, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County Surveyors Office in 1970, monumented with an iron post 1" dia., firmly set, projecting 16" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W S1/4C S31 T33S 1970,
(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 166700

PRIMARY CORNER DESCRIPTION A.P. #1 on N. bdy. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the original bearing trees:
A Fir stump 18" dia., bears N.10°W., 23½ lks. dist., with scribe marks ¼ SC BT visible on open weathered double blaze. (Record, N.30°E., 19 lks.)
A Fir stump 10" dia., bears S.27°W., 18 lks. dist., with scribe marks ¼ SC visible on partially healed double blaze.
and bearing trees mkd. by the County
A Fir 8" dia., bears N.39°E., 19 lks. dist., with scribe marks ¼ SC 31 CS BT visible on partially healed double blaze.
A Fir 9" dia., bears N.26°W., 42½ lks. dist., with scribe marks ¼ SC 31 CS BT visible on partially healed double blaze.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
AP 1
T 32 S R 4 W
S 31
1975
Reset county iron post alongside iron post.