

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 172700

PRIMARY CORNER DESCRIPTION C C cor. for Secs. 31 & 32 only T32-4

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8534)

Set a basalt stone, 14 x 10 x 10 ins., 9" in the ground, for a closing corner of secs. 31 and 32, marked C C on N., with 1 groove on W. and 5 grooves on E. faces; from which

A Fir 30" dia., bears N.62½°E., 97 lks. dist., mkd. T32S R4W S32 BT.

A Fir 12" dia., bears N.23½°W., 25 lks. dist., mkd. T32S R4W S31 BT.

This corner is on an E. slope, 75 ft. above ridge.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16537)

The original closing cor. of secs. 31 and 32, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees:

A Fir snag 35" dia., bears N.68½°E., 91 lks. dist., with illegible scribe marks visible on burned blaze. (Rec., N.62½°E., 97 lks.)

A Fir 25" dia., bears N.23½°W., 25 lks. dist., with scribe mark B visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 32 S R 4 W

C C

S 31 S 32

S 6

T 33 S

1975

from which a new bearing tree

A Fir 32" dia., bears N.34½°E., 112 lks. dist., mkd. T32S R4W S32 CC BT.