

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8939)

-----

Set basaltic stone 18 x 10 x 8 ins., 12" in the ground, for cor. to secs. 7, 8, 17 and 18, marked with 4 notches on S. and 5 notches on E. edges, from which

- A Fir 18" dia., bears N.50°E., 48 lks. dist., marked T33S R4W S8 BT.
- A Fir 22" dia., bears S.29°E., 13 lks. dist., marked T33S R4W S17 BT.
- A Fir 36" dia., bears S.80°W., 15 lks. dist., marked T33S R4W S18 BT.
- A Fir 20" dia., bears N.62°W., 60 lks. dist., marked T33S R4W S7 BT.

BLM remonumentation by James E. Jelley, Cadastral Surveyor, Group #350, April 1962 - (DCSO records Vol. 33 Page(s) 13928-29)

-----

The Sec. cor., monumented with a basalt stone, 18 x 10 x 8 ins., firmly set 8" in the ground, marked with 4 notches on S. and 5 on E. edges, from which the remaining original bearing trees:

- A Fir 30" dia., bears S.42°E., 18 lks. dist., with no marks remaining on opened blaze. Reblaze and mark T33S R4W S17 BT, alongside old blaze. (Rec. S.29°E., 13 lks.)
- A sawed Fir stump, 25" dia., bears S.80°W., 15 lks. dist., with no marks remaining.
- A down Fir 25" dia., bears N.62°W., 60 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 33 S R 4 W  
    S 7 S 8      
 S 18 S 17  
 1962

from which

- A Noble Fir 6" dia., bears N.36°E 52 lks. dist., marked T33S R4W S8 BT.
  - A Noble Fir 6" dia., bears S.47½°W., 93 lks. dist., marked T33S R4W S18 BT.
  - A Noble Fir 8" dia., bears N.23½°W., 34 lks. dist., marked T33S R4W S7 BT.
- Deposit the original corner stone alongside the iron post.

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - John Powell, W. Penley and  
Jack Heritage, crew - June 5, 1970 - C.S. File 54/114-8

-----

Found - 1962 cadastral brass cap alongside corner stone.  
8" N.Fir S.47½°W., 61.4 ft., shows good scar.  
10" N.Fir N.23½°W., 22.4 ft., shows good scar.  
6" N.Fir N.36°E., 39.3 ft. (Rec. 34.2 ft.) bark  
scribed "T33S R4W S8 BT"  
26" D.Fir S.42°E., 11.9 ft. This tree cut open,  
scribe visible. (dead top)  
New BT - 36" N.Fir S.65°E., 30.2 ft. mkd. T33S R4W S17 CS BT