

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8942)

Set a basaltic stone 18 x 10 x 8 ins., 12" in the ground, for cor. to secs. 5, 6, 7 and 8, marked with 5 notches on S. and E. edges, from which
A Y.Pine 24" dia., bears N.5°E., 50 lks. dist., marked T33S R4W S5 BT.
A Y.Pine 24" dia., bears S.49°E., 17 lks. dist., marked T33S R4W S8 BT.
A Y.Pine 24" dia., bears S.44°W., 148 lks. dist., marked T33S R4W S7 BT.
A Y.Pine 12" dia., bears N.55°W., 117 lks. dist., marked T33S R4W S6 BT.

Survey by John Markham, Jr. - Wit: Geo. Blomgren - For: Stomar Lumber - July 28, 1954 - C.S. File 41/322

Determined by O.B.T.s
A 26" Y.Pine snag bears S.49°E., 11.0 ft., found scribe.
A 38" Y.Pine bears N.5°E., 33.0 ft.
A 16" Y.Pine bears N.77°W., 73.0 ft.
At corner point found stone and made a large pile of stones. from which
A 10" Y.Pine bears S.5°W., 12.0 ft. mkd. S7 BT.
A 9" Fir bears S.45°E., 20.0 ft. mkd. S8 BT.
Corner lies on top of ridge at the East end of rocky opening.

Douglas Co. Surveyors Office, John Powell, Willie Penley and Jack Heritage, crew - June 4, 1970 - C.S. File 54/114-1

Found - 18x10x8 stone, firmly set, mkd. with notches on N. and S. sides.
Orig. 24" now 30" Y.Pine N.5°E., 33.0 ft. shows good scar.
Orig. 24" Y.Pine now snag S.56°E., (S.49°E) 11.2 ft. scribe visible.
Orig. 12" now 15" Y.Pine N.55°W., 75.2 ft. (Rec. 77.2 ft.) Orig. distance may be slope distance.
9" now 9" D.Fir S.45°E., 21.3 ft. (Rec. S.45°E., 20.0 ft.) shows good scar.
10" now 11" Y.Pine S.2½°W., 12.7 ft. (Rec. S.5°W., 12.0 ft.) parts of scribe marks visible.

(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 4 W

S 6 | S 5

S 7 | S 8

1970

All bearing trees OK and tagged.

This corner lies on very rocky ridge at E. end of opening.

Fd. OK by BLM, June 1979, C.S. File 58/202

Fd. OK, H. Pieske, May 1993, M 117-13

Fd. Ok by Ken Hoffine, 3/2005 - M147-57 A&B