

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8945)

-----  
Set a basaltic stone 24 x 10 x 10 ins., 18" in a mound of stone and earth for ¼ sec. cor. marked ¼ on W. face, from which

A Y.Pine 18" dia., bears N.66°E., 98 lks. dist., marked ¼ S BT.

A Y.Pine 2 ft. dia., bears S.2°W., 72 lks. dist., marked ¼ S BT.

Douglas Co. Surveyors Office, John M. Powell, W. Penley, J. Heritage, crew - June 4, 1970 - C.S. File 54/114-4

-----  
Found - 24x10x10 stone mkd. "4", lying in mound of stone with "4" on E. face.

18" now 24" Pine N.73°E., (Rec. N.66°E.) 64.7 ft.  
Tree opened earlier "S" visible.

24" Pine, now snag, S.1½°E., (Rec. S.2°W) 47.5 ft., scribe visible, "¼ S BT".

Counting rings of NE BT shows tree old enough for orig. BT. Call of 1 chain is good to top of ridge. Renew by intersection of distance of BTs as there is a lot of local attraction in area.

Set Brass cap at cor. mkd: County Surveyors Office

T 33 S R 4 W

¼ S 6 | S 5

1970

Brass cap set in mound of stone.

New BT - 10" Pine N.31°W., 9.7 ft. "¼ S6 CS BT"

Cor. Fd. OK, BLM Millsite survey by Larry Friar, July/Nov. 1983 (DCSO records, Vol. 45 pages 17240)

Fd. Ok by Ken Hoffine, 3/2005 - M147-57 A&B