

PRIMARY CORNER DESCRIPTION A.P. #2 N. bdy. Sec. 5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by McKenzie and Eckelson, Deputy Surveyors under Contract #328, dated June 17, 1879 (DCSO records Vol. 20 Page(s) 8466)

Set post corner to secs. 31 and 32, from which
A Fir 30" dia., bears N.50°W., 29 lks. dist.
A Fir 24" dia., bears N.48°E., 36 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8478-79)

Standard corner of secs. 31 and 32, which is a post badly decayed; bearing trees standing and agreeing with the description of the surveyor general. I reestablish this corner at the same point as follows:
Set a basalt stone, 12 x 10 x 10 ins., 8" in the ground, for standard cor. of secs. 31 and 32, marked S. C. on N., with 1 groove on W., and 5 grooves on E. faces; from which
A Fir 18" dia., bears N.48°E., 36 lks. dist., marked T32S R4W S32 BT.
A Fir 24" dia., bears N.50°W., 29 lks. dist., marked T32S R4W S31 BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16536)

The former standard cor. of secs. 31 and 32, changed to an angle point by Chapman and Nicklin, monumented with a basalt stone, 12x10x10 ins., loosely set 3" in the ground, mkd. SC on N., 5 grooves on E. and 1 groove on W. faces, from which the remains of the original bearing trees:
A Fir snag 23" dia., bears N.50°E., 36 lks. dist., with scribe marks T32S visible on partially opened double blaze. (Rec. N.48°E.)
A Fir snag 30" dia., bears N.50°W., 29 lks. dist., with scribe marks SC T32S R4W S32 visible on burned and open double blaze.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked
AP 2
T 32 S R 4 W
S 32
1975

from which new bearing trees

(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 224700

PRIMARY CORNER DESCRIPTION A P #2 on N. bdy. Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 10" dia., bears N.36°E., 22½ lks. dist., mkd. AP2
S32 BT.
A Cedar 6" dia., bears N.59°W., 34 lks. dist., mkd. AP2
S32 BT.
Deposit corner stone alongside iron post.