

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8943)

-----  
Set a basaltic stone, 15 x 8 x 6 ins., 10" in the ground, for 1/4 sec. cor. marked 1/4 on N. side, from which  
A Cedar 9" dia., bears N.55°E., 31 lks. dist., marked 1/4 S BT.  
A Fir 24" dia., bears S.38°W., 22 lks. dist., marked 1/4 S BT.  
This cor. is about 75 ft. above foot of descent at 19.20 chs.

Douglas Co. Surveyors Office, John Powell, W. Penley, and J. Heritage, crew - June 4, 1970 - C.S. File 54/114-5

-----  
Found - Stone 15x8x6 mkd. "1/4" on North.  
9" now 22" Cedar N.55°E., 20.4 ft., shows good scar.  
24" now 36" D.Fir S.38°W., 14.5 ft. shows good scar.

Set Brass cap at cor. md: County Surveyors Office  
T 33 S R 4 W  
1/4 S 5 D o u g C o  
S 8 J a c k C o  
1970  
New BT - 6" Cedar S.70°W., 15.7 ft. mkd. "1/4 S8 DCS BT".

Fd. OK, by BLM, June 1979, C.S. File 58/202

Fd. OK, H. Pieske, May 1993, M 117-13