

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 269700

PRIMARY CORNER DESCRIPTION A.P. #1 on N. bdy. sec. 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by McKenzie and Eckelson, Deputy Surveyors under Contract #328, dated June 17, 1879 (DCSO records Vol. 20 Page(s) 8465)

Set post for $\frac{1}{4}$ sec. corner, from which
A Fir 20" dia., bears N.68°W., 10 lks. dist.
A Cedar 24" dia., bears S.70°E., 24 lks. dist.

Cor. Fd. in GLO survey by Sharp in 1893 (DCSO records, Vol. 21 Pg. 8936)

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8479)

Post destroyed, bearing trees standing from which I reestablish this $\frac{1}{4}$ sec. corner as follows:
Set a basalt stone 14 x 10 x 8 ins., 9" in the ground for standard $\frac{1}{4}$ sec. corner, marked S.C. $\frac{1}{4}$ on N. face; from which
A Cedar 16" dia., bears S.45°E., 26 lks. dist., marked S.C. $\frac{1}{4}$ S BT.
A Fir 20" dia., bears N.68°W., 10 lks. dist., marked S.C. $\frac{1}{4}$ S BT.

Douglas Co. Surveyors Office - John M. Powell, W. Penley and J. Heritage, crew - May 15, 1970 - C.S. File 54/114-29

Found - 16" now 24" Cedar S.45°E., 16.5 ft. opened for scribe, burnt and rotted face, but found definite reverse scribing.
20" D.Fir now stump, N.68°W., 6.6 ft., no marks found.

Set Brass cap at cor. mkd: County Surveyors Office
T32S R4W S $\frac{1}{4}$ C S 32
T33S

1970
New BTs -14" D.Fir N.15°W., 30.6 ft. mkd. S $\frac{1}{4}$ C S32 CS BT.
8" D.Fir S.61°E., 18.4 ft. mkd. S $\frac{1}{4}$ C CS BT.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16534-35)

The former standard $\frac{1}{4}$ sec. cor. of sec. 32, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County in 1970, monumented with an iron post, 1" dia.,
(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 269700

PRIMARY CORNER DESCRIPTION A.P. #1 on N. bdy. Sec. 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

firmly set, projecting 18" above ground, with brass cap mkd.
COUNTY SURVEYORS OFFICE T32S R4W S1/4C S32 T33S 1970, from
which the remains of the original bearing trees:

A Fir stump 24" dia., bears N.62½°W., 12 lks. dist., with
healed blaze. (Record, N.68°W., 10 lks.)

A Cedar 24" dia., bears S.45°E., 26 lks. dist., with
partially opened and burned blaze, no marks visible.
and bearing trees mkd. by the County

A Fir 16" dia., bears N.15°W., 45½ lks. dist., with scribe
marks 4 BT visible on partially healed double blaze.

A Fir 10" dia., bears S.65½°E., 27 lks. dist., with scribe
marks S ¼ C CS BT visible on partially healed double
blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in
the ground, with brass cap marked AP 1

T 32 S R 4 W

S 32

1975

Reset county iron post alongside iron post.