

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8934)

-----

Set a basaltic stone 20 x 12 x 10 ins., 15" in the ground, for cor. to secs. 4, 5, 8 and 9, marked with 5 notches on S. and 4 notches on E. edges, from which

A Fir 24" dia., bears N.30°E., 25 lks. dist., marked T33S R4W S4 BT.

A W.Fir 12" dia., bears S.60°E., 23 lks. dist., marked T33S R4W S9 BT.

A Fir 8" dia., bears S.50°W., 72 lks. dist., marked T33S R4W S8 BT.

A Fir 14" dia., bears N.19°W., 38 lks. dist., marked T33S R4W S5 BT.

BLM remonumentation by James E. Jelley, Group #350, April, 1962 (DCSO records Vol. 33 Page(s) 13926-27)

-----

The Sec. cor., monumented with a basalt stone, 20 x 12 x 10 ins., firmly set 10" in the ground, marked with 5 notches on S. and 4 notches on E. edges, from which the original bearing trees:

A Fir 30" dia., bears N.30°E., 25 lks. dist., with a healed blaze.

A Fir 24" dia., bears S.60°E., 23 lks. dist., with a healed blaze.

A Fir 20" dia., bears S.50°W., 72 lks. dist., with a healed blaze.

A down Fir, 25" dia., bears N.19°W., 38 lks. dist., with scribe marks T33S R visible on partly healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

T 33 S R 4 W  
S 5 S 4  
S 8 S 9  
1962

from which

A Fir 9" dia., bears N.59°W., 80 lks. dist., marked T33S R4W S5 BT.

Deposit the original corner stone alongside the iron post.

Douglas County Surveyors Office, John Powell, W. Penley, J. Heritage, crew - June 4, 1970 - C.S. File 54/114-3

-----

Found - 1962 Cadastral brass cap, properly mkd. and set.  
(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Orig. 21" D.Fir, alive, S.60°E., 15.2 ft. shows good scar.  
Orig. 28" D.Fir, alive, N.30°E., 16.5 ft. shows good scar.  
Orig. 16" D.Fir snag, dead, S.50°W., 47.5 ft. shows scar and has been opened.  
12" R.Fir, alive, N.59°W., 52.8 ft. scribe visible on nearly healed blaze.  
New BT - 11" R.Fir S.50°W., 29.2 ft. mkd. T33S R4W S8 DCS BT.  
From this corner, a mound of stone 2 ft. at the base, 1 ft. high, bears N.13½°W., 10.4 ft. and a mound of stone 1½ ft. at the base and 1 ft. high bears N.71°E., 10.7 ft.

Fd. OK, by BLM, June 1979, C.S. File 58/202