

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C C cor. Secs. 4 & 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8936-37)

The point for closing cor. to secs. 4 and 5 and set a basaltic stone, 24 x 12 x 8 ins., 8" in the ground, marked C C with 4 notches on E. and 2 notches on W. edges, from which
A Cedar 18" dia., bears S.64°E., 8 lks. dist., marked T33S R4W S4 BT.
A Fir 6" dia., bears S.63°W., 34 lks. dist., marked T33S R4W S5 BT.
A Cedar 10" dia., bears N.22°E., 8 lks. dist., marked T33S R4W C C S4 and 5 BT.

Douglas Co. Surveyors Office - John Powell, W. Penley and J. Heritage, crew - June 17, 1970 - C.S. File 54/114-28

Found - 10" now 13" Cedar N.27°E., (Rec. N.22°E) 5.3 ft., scribe visible.
18" now 22" Cedar S.64°E., 5.3 ft., scribe visible.
6" now 9" D.Fir S.63°W., 24.4 ft., shows good scar.
24" x 12" x 8" stone, mkd. "CC".

Set Brass cap at cor. mkd: County Surveyors Office
T32S R4W CC $\frac{S\ 33}{S\ 5\ S\ 4}$
1970

New BT - 22" Laurel N.55°W., 14.5 ft. mkd. T32S R4W S33 CSBT.
All other BTs OK and tagged.
This corner lies about 70.0 ft. West of ravine.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16521-22)

(25.67 chs.)

The orig. closing cor. of secs. 4 & 5, perpetuated and recorded by the County in 1970, monumented with an iron post, 1" dia., firmly set, projecting 20" above ground, and in a mound of stone, 1½ ft. base, 1 ft. high, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W S33 S5 S4 CC T33S 1970, from which the original bearing trees:

A Cedar 13" dia., bears N.27°E., 8 lks. dist., with scribe marks T33S R4W CC visible on partially opened blaze. (Rec. N.22°E.)

A Cedar 26" dia., bears S.64°E., 8 lks. dist., with scribe marks T33S R4W S4 visible on partially opened blaze.

(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 300700

PRIMARY CORNER DESCRIPTION C C cor. Secs. 4 & 5 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 11" dia., bears S.63°W., 33 lks. dist., with healed blaze. (Rec. 34 lks.)
and a bearing tree mkd. by the County
A Madrone 22" dia., bears N.58°W., 22 lks. dist., with scribe marks 32S R4W S33 CS BT visible on partially healed double blaze.

(25.78 chs., N.0°08'W)
True point for the closing cor. of secs. 4 and 5.
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked

T 32 S
S 33
S 5 | S 4
C C
T 33 S R 4 W
1975

from which
A Cedar 17" dia., bears S.46 3/4°E., 21½ lks. dist., mkd. T33S R4W S4 CC BT.
A Fir 10" dia., bears S.57¼°W., 53 lks. dist., mkd. T33S R4W S5 CC BT.

Harvey M. Christensen - For: Future Logging Co. & Silver Butte Timber Co. - Feb. 2024 - M183-61

Orig. Closing corner
Found - 2.5" DCS0 BC, 8' above grade, 1961
BTs - 28" W.Cedar S.64°E., 5.3 ft. healed face
16" W.Cedar N.27°E., 5.3 ft. healed face

True Closing corner
Found - 2.5" BLM BC, _ above grade, 1975
BTs - 19" W.Cedar S.47°E., 14.2 ft., healed face.
16" D.Fir S.57°W., 35.1 ft., healed face.