

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 374700

PRIMARY CORNER DESCRIPTION C C cor. Secs. 33 & 34 only, T32-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8509)

-----  
The standard corner of secs. 33 and 34, which is a post 4" sq., 24" above ground, marked and witnessed as described by the surveyor general.

Set a basalt stone 12 x 10 x 8 ins., 8" in the ground for a closing corner of secs. 33 and 34, marked C.C., T32S R4W on N.; S33 on W.; and S34 on E. faces; with 3 grooves on E. and W. faces, from which

A Fir 10" dia., bears N.8°E., 32 lks. dist., marked T32S R4W S34 BT.

A Fir 30" dia., bears N.37½°W., 30 lks. dist., marked T32S R4W S33 BT.

This closing corner is on top of spur sloping S., 100 ft. below trail.

Douglas Co. Surveyors Office - John Powell, W. Penley and J. Heritage, crew - June 17, 1970 - C.S. File 54/114-17

-----  
Found - 30" Fir now snag N.37°W., 20.0 ft. scribe visible, burnt face.

No trace of other bearing trees.

Set Brass cap at cor. mkd. County Surveyors Office

Douglas Co.

T32S R4W CC S 33 | S 34  
T33S S 4

Jack. Co.

1970

New BTs -4" D.Fir N.20°E., 9.7 ft. mkd. S34 CC CS BT.

8" D.Fir S.4°E., 14.5 ft. mkd. T33S R4W S4 CS BT.

10" D.Fir N.64°W., 42.5 ft. mkd. T32S R4W S33 CC CS BT.

This corner lies on small spur, running South.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16546)

-----  
(59.865 chs.)

The original closing cor. of secs. 33 and 34, perpetuated and recorded by the County in 1970, monumented with an iron post, 1" dia., firmly set, projecting 30" above ground, and in a mound of stone, 2½ ft. base, 1½ ft. high with brass cap mkd. COUNTY SURVEYORS OFFICE DOUG CO T32S R4W CC S33 S34 S4 T33S JACKSON CO 1970, from which the remains of an original bearing trees: (Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 374700

PRIMARY CORNER DESCRIPTION C C cor. Secs. 33 & 34 only, T32-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir snag, 36" dia., bears N.37½°W., 30 lks. dist., with scribe marks 32S R4W BT visible on burned blaze. and bearing trees mkd. by the County

A Fir 5" dia., bears N.20°E., 15 lks. dist., with scribe marks S34 CC CS BT visible on partially healed blaze.

A Fir 9" dia., bears S.4°W., 22½ lks. dist., with scribe marks 33S R4W visible on partially healed double blaze.

A Fir 12" dia., bears N.64°W., 66 lks. dist., with scribe marks T32S R4W S33 CC CS BT visible on partially healed double blaze.

(60.22 chs. S.0°50'E)

True point for the closing corner of secs. 33 and 34.

Set an iron post, 28" long, 2½" dia., 6" in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:

T 32 S R 4 W  
C C  
S 33 | S 34  
S 4  
1975

from which

A Cedar 12" dia., bears N.41½°E., 74½ lks. dist., mkd. T32S R4W S34 CC BT.

A Fir 9" dia., bears N.28°W., 26½ lks. dist., mkd. T32S R4W S33 CC BT.

Harvey M. Christensen - For: Future Logging Co. & Silver Butte Timber Co. - Feb. 2024 - M183-61

Found - 2.5" BLM BC in mound of stone, 1975.

BTs - 15" W.Hem S.66°E. 27.3 ft blazed & scribed "X" "BT"

12" D.Fir S.65°W., 19.3 ft blazed & scribed "X" "BT"

14" W.Cedar N.41.5°E., 49.2 ft. healed face

7" D.Fir N.28°W., 17.5 ft. scribing visible, dying.