

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by McKenzie and Eckelson, Deputy Surveyors, under Contract #328, dated June 17, 1879 (DCSO records Vol. 20 Page(s) 8465)

-----  
Set post for corner to secs. 33 and 34, from which  
A Fir 18" dia., N.45°E., 19 lks. dist.  
A Chinquapin 8" dia., N.36°W., 59 lks. dist.

Douglas Co. Surveyors Office - John Powell, W. Penley and J. Heritage, crew - May 19, 1970 - C.S. File 54/114-34

-----  
Found - No trace of NW BT.  
18" D.Fir now dead stob, N.45°E., 12.5 ft. upper face open, old rotten scribe visible "S" and other marks.

Set Brass cap at cor. mkd: County Surveyors Office  
Doug. Co.  
T32S<sub>1/4</sub> S 33 | S 34  
T33S<sub>1/4</sub> S SC 1970  
Jack. Co.

New BTs -24" D.Fir N.48°E., 19.5 ft. mkd. "T32S R4W S SC S34 CS BT".  
32" D.Fir N.8°W., 21.4 ft. mkd. "T32S R4W S SC S33 CS BT".

This corner lies approx. 125.0 ft. West of draw.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16530-31)

-----  
The former standard cor. of secs. 33 and 34, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County in 1970, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W S33 S34 SSC T33S 1970, from which the remains of an original bearing tree:

A Fir snag 18" dia., bears N.45°E., 19 lks. dist., with scribe marks BT visible on opened double blaze.  
and bearing trees mkd. by the County

A Fir 27" dia., bears N.49°E., 29½ lks. dist., with scribe marks T32S R4W SSC34 CS BT visible on pitched over double blaze.

A Fir 30" dia., bears N.7°W., 31 lks. dist., with scribe marks T32S R4W SSC33 CS BT visible on pitched over double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 24 ins. in the ground, with brass cap marked (Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 423700

PRIMARY CORNER DESCRIPTION A.P. #2, N. bdy. Sec. 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

AP 2  
T 32 S R 4 W  
S 34  
1975  
Reset county iron post alongside iron post.