

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 3 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud,  
Cadastral Surveyors, Under Group #865, surveyed July/Oct.  
1975 (DCSO records Vol. 42 Page(s) 16520-21)

-----  
The point for the ¼ sec. cor. of sec. 3 only, T33S R4W, is at  
midpoint on the N. bdy. of sec. 3  
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in  
the ground, and in a mound of stone, 4 ft. base to top, with  
brass cap marked

1/4 S 3  
T 33 S R 4 W  
1975

from which

A Cedar 8" dia., bears S.70½°E., 26½ lks. dist., mkd. ¼ S3  
BT.

A Fir 18" dia., bears S.44°W., 281½ lks. dist., mkd. ¼ S3  
BT.