

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T32-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8491)

Set a basalt stone 10 x 8 x 8 ins., 8" in the ground for a closing corner of secs. 34 and 35, marked C.C. on N. face, with 4 grooves on W. and 2 grooves on E. faces, from which
A Fir 24" dia., bears N.45°E., 96 lks. dist., marked T32S R4W S35 BT.
A Fir 30" dia., bears N.44°W., 50 lks. dist., marked T32S R4W S34 BT.
This corner is on top of a spur sloping E., 200 ft. above creek.

Survey by Lorne Swearingen - For: Southern Oregon Plywood - July 31, 1968 - C.S. File 55/85

The SE Sec. cor. of Sec. 34, T32S R4W was a stone which has been destroyed by a cat fire trail on a BLM timber sale. I replaced the corner as follows: (used compass and steel tape)
Set 1" x 30" Iron pipe, 10" above ground level.
Two original bearing trees remains:
24" D.Fir bears 96 lks. dist.
30" D.Fir bears 50 lks. dist.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16544)

(59.34 chs.)
True point for the closing cor. of secs. 34 and 35
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked
T 32 S R 4 W
C C
S 34 S 35
S 3
T 33 S
1975
from which
A Fir 4" dia., bears N.36°E., 25½ lks. dist., mkd. X BT.
A Fir 10" dia., bears N.78°W., 78 lks. dist., mkd. T32S R4W S34 BT.
From this point, the original closing cor. of secs. 34 and 35, bears S.0°13'E., 0.025 chs. dist., perpetuated by
(Cont. Next Page)

TOWNSHIP 33 RANGE 04 POINT IDENTIFIER # 474700

PRIMARY CORNER DESCRIPTION C C for Secs. 34 & 35 only, T32-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

person(s) unknown, monumented with a iron pipe, 3/4" dia., firmly set, projecting 12" above ground, from which the original bearing trees:

A Fir 37" dia., bears N.45°E., 96 lks. dist., with healed blaze.

A Fir 35" dia., bears N.44°W., 50 lks. dist., with healed blaze.