

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & Sec. 1, T33-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Butler Ives and George W. Hyde, under Contract #39, dated January 4, 1854 - (DCSO records Vol. 21 Page(s) 8949)

Set ¼ sec. post, from which
A B.Oak 14" dia., bears S.32°W., 48 lks. dist.
A B.Oak 12" dia., bears S.60°E., 13 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy, J.M. Powell and crew - March 19, 1968 - C.S. File 49/112

Found - Orig. 14" B.Oak now stump, S.34°W. (Rec. S.32°W.)
31.7 ft., opened for scribe "BT".
Orig. 12" now 23" B.Oak, S.60°E., 8.6 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office
Doug. Co.
R T 33 S R
6 ¼ S 1 | S 6 5
W Jos. Co. W

New BT - 11" D.Fir S.31°W., 24.3 ft. mkd. ¼ S1 CS BT.
Reblazed and rescribed:
23" B.Oak S.60°E., 8.6 ft. mkd. ¼ S6 CS BT.
Corner lies approx. 35.0 ft. S. of ridge top, ridge running E-W.

Fd. & used on BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20358-9)

Fd. Ok by K DeGroot, 7/2006 - M151-7