

PRIMARY CORNER DESCRIPTION AP North bdy T33-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, S.A. Bilow, crew - For: C & D Lumber Co. - Aug. 1958 - C.S. File 49/112 and M 12-51

Original BTs not found. Set by proportionate measurement.
Set Brass cap at cor. mkd: County Surveyors Office 1958
South ¼ S31 T32S R5W
New BTs -10" R.Fir bears N.37°E., 3.5 ft. scribed ¼ S31 CSBT
10" Laurel bears N.27½°W., 33.2 ft. scribed ¼ S31 CS
BT.

BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20355)

A point established & recorded by the Douglas Co. Surveyor's Office in 1958, as the ¼ sec. cor. of sec. 31 only, T32-5, monumented with an iron post, 1½" dia., firmly set, projecting 16" above ground, in a collar of stone, 2 ft. base 6" high, with brass cap marked as noted in 1958 ren., from which the BTs mkd. by the DCSO
A Fir, 17" dia., bears N.37°E., 5½ lks., with healed double blaze.
A Madrone, 12" dia., bears N.27½°W., 50½ lks., with healed double blaze.

This point is at proportionate distance for the 1854 Ives & Hyde standard ¼ sec. cor. of secs. 6 & 31; there is no remaining evidence of the orig. corner. This corner now becomes an angle point on the N. bdy of the Tp., and does not control the subdivision of either section.

N.89°52'00"W., 1.28 chs.

Point for the ¼ sec. cor. of sec. 31 only, T32S R5W
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap marked:
T32S R5W
¼ S 31
1989

from which
A Fir, 16" dia., bears N.55°E., 14 lks., mkd: ¼ S31 BT.
A Fir, 14" dia., bears N.18°W., 20 lks., mkd: ¼ S31 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

continued next page

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 143700

PRIMARY CORNER DESCRIPTION AP North bdy T33-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 7/6/2000 - C.S. File 66/16-16

Found - 1958 DCSO BC/IP (set & marked as S ¼ S31 in 1958)
protrudes 16" above a mound of stone. **1989 BLM**
survey designates this corner as an angle point
on line. We stamp out "¼ South" and add "AP" S6
DCSO 2000". Cap marked:

COUNTY SURVEYORS OFFICE

T32S

S 31 AP
S 6

T33S R5W

DCSO 2000

1958

See 1989 BLM Line notes page 20355

1958 DCSO BTs

10" now 19" D.Fir with a fully healed double blaze
bears N.37°E., 3.6 ft.

10" now 13" Madrone with a fully healed double blaze
bears N.27½°W., 32.6 ft. (rec. N.27½°W. 33.3 ft.)

New - 10" dia., Madrone double blazed & scribed "AP S6 CS
BT" bears S.41°E., 22.4 ft.

Note - BTs from 1958 fully healed, we did not axe out 1958
scribing.

Fd. Ok by K DeGroot, 7/2006 - M151-7