

TOWNSHIP 33 RANGE 05 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION C C for Secs. 5 and 6 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (Cor. set June 29, 1894) (DCSO records Vol. 21 Page(s) 8998-99)

-----  
The closing cor. to secs. 5 and 6, Set a basaltic stone 18 x 10 x 5 ins., 12" in the ground for closing cor. to secs. 5 and 6 marked C C with 5 notches on the E. and 1 notch on the W. edges, from which

- A Fir 36" dia., bears S.55°E., 62 lks. dist. marked T33S R5W S5 BT.
- A Fir 24" dia., bears S.56°W., 72 lks. dist. marked T33S R5W S6 BT.
- A Fir 30" dia., bears N.38°E., 26 lks. dist. marked T33S R5W C C S5 and 6 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey, S.A. Bilow, crew - For: C & D Lumber Co. - Aug. 19, 1958 - C.S. File 49/112 and M 12-51

-----  
Found - Stone at corner as recorded, except I do not find the "CC"

- Orig. 36" now 40" Fir stump S.55°E., 40.9 ft. I open and find good scribing "R5W"
- Orig. 30" now 36" Fir N.38°E., 17.2 ft. Shows good scar, I do not open.

Set Brass cap at cor. mkd: County Surveyors Office

S 6 | S 5  
-----  
1958

- New BTs -24" Fir bears S.12°E., 18.0 ft. scribed T33S R5W CC S5 CS BT.
- 6" Acorn Oak S.44°W., 12.2 ft. scribed T33S R5W CC S6 CS BT.

Fd. cor. OK, DCSO, Aug. 1967 C.S. File 53/52-16

Fd. & used on BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20354)